

Scan-X Corporate 160KV 5030

Multi-Energy X-Ray Security Scanner



www.scanxsecurity.com

Applications

Briefcase, handbags, mail, etc. inspection, widely used in:

- Government
- Court
- Prisons
- Post Office
- Asset Protection
- Exhibitions

Highlights

- Multi-energy, 34mm steel penetration
- 0.0787mm high-definition image
- Compact, portable and convenient to move
- Ultra-low X-Ray leakage, complying with domestic and international safety standards
- Double screen joint display, wider view and longer recognition time
- Drugs and explosives auto inspection (SX-DEI)
- Hi-spot for image best contrast and HDA to alert dangerous items
- SX Scale to make sure image in original shape without distortion
- Ultra-thin object scanning
- Modular design, self-diagnosis for important parts like X-Ray generator, detection boards array, light barrier
- Convenient software and humanised hardware, special keyboard, zoom and move by mouse
- SX-GSM (optional)
- Threat image projection (SX-TIP) (optional)
- Video monitoring system (SX-VMS) (optional)
- Energy saving device (optional)




Scan-X Security Limited,

Unit 5, Bentley Lane Industrial Estate, Bentley Lane, Walsall WS2 8TL.

T: 01922 616360 F: 0121 275 6048 E: sales@scanxsecurity.com www.scanxsecurity.com

Scan-X Corporate 160KV 5030 Multi-Energy X-Ray Security Scanner




Specification	
Tunnel Size	505mm (W) x 305mm (H)
Conveyor Speed	0.2m/s: up to 0.3m/s
Max. Conveyor Load	120kg (evenly distributed)
System Noise	<55dB

Performance Index	
Resolution	0.0787mm Metal Wire (AWG40)
Penetration	34mm Steel
Leakage	<0.1 μ Sv/H
Dose Per Inspection	<2.62 μ Sv
Image Resolution	1280 x 1024/24Bits
Film Safety	ISO 1600 guaranteed

Image Processing		
Image Processing	<ul style="list-style-type: none"> Colour / Black & White Multi-energy Organic/Inorganic Strip Edge Enhancement 	<ul style="list-style-type: none"> Super Enhancement Negative H/L Penetration Gray Level Scanning
Material Classification	<ul style="list-style-type: none"> Organic: Orange Inorganic: Blue 	<ul style="list-style-type: none"> Light Metal and Mixture: Green High Density Material: Black or Red
Zoom	<ul style="list-style-type: none"> 1-32 Times for any zone, Dynamic, Smooth and Stepless Full screen zoom by one click 	
Double-screen Display	<ul style="list-style-type: none"> Double-screen Joint Display Colour + Black and White Display Double-screen Copy Display 	
Image Recall	<ul style="list-style-type: none"> 20 Screens 	
Image Storage	<ul style="list-style-type: none"> 100000 images (at least) Image Simulated Playback Image Search 	<ul style="list-style-type: none"> Image Export Image Batch Conversion (to .jpg)
Additional Features	<ul style="list-style-type: none"> Customised Shortcuts Image Retrieval Package Counter Multi-level User Management 	<ul style="list-style-type: none"> User Report Management Self Diagnosis Maintenance Warning Date/time Display
Display	<ul style="list-style-type: none"> Quick Shutdown Multi-language X-Ray Work Time Counter System Work Time Counter 	
	<ul style="list-style-type: none"> High Resolution 19" LCD 	

X-Ray Generator	
X-Ray Direction	Upward
Tube Voltage	100-160kV (adjustable)
Tube Current	0.3 ~ 1.2 mA (adjustable)
Cooling / Duty	Sealed Oil Cooling / 100%
Beam Launch Angle	80°

Installation Data	
Storage Temperature / Humidity	-20°C ~ +50°C / 10% ~ 95% (non-condensing)
Working Temperature / Humidity	0°C ~ +45°C / 10% ~ 95% (non-condensing)
Working Voltage	AC 220V (-15% ~ +10%), 50Hz/60Hz \pm 3Hz
Power	0.4kVA



Note: The appearance and specifications are subject to actual product.



Scan-X Security Limited,

Unit 5, Bentley Lane Industrial Estate, Bentley Lane, Walsall WS2 8TL.

T: 01922 616360 F: 0121 275 6048 E: sales@scanxsecurity.com www.scanxsecurity.com