PD140

ENHANCED HAND HELD METAL DETECTOR

FEATURE HIGHLIGHTS

- High Sensitivity
- Detection of both Magnetic and Non-Magnetic Metals
- Optical, Acoustical and Vibration Alarm
- Long Battery Life
- Very High Reliability
- Easy to Use
- Self-Calibrating
- Fast Inductive Battery Charger (optional for PD140VR model)





THE SPECIAL ERGONOMIC SHAPE OF THE DEVICE ALLOWS INSPECTION WITHOUT THE INTERFERENCE OF THE OPERATOR'S FINGERS











V140 CARRYING CASE

PD 140

PD140 ENHANCED HAND HELD METAL DETECTOR



The PD140 Enhanced Hand Held Metal Detector is a **high sensitivity device designed to detect magnetic and non-magnetic metal masses**.

The unit can be used to detect weapons, detonators and other small pieces of metal concealed in baggage or correspondence.

The bidirectional detection probe allows both sides to detect metals evenly. The sensitivity of the surface is enhanced by the shape making operation of the device reliable and easy to operate.

The PD140 Metal Detector is **available in two standard sensitivity versions**: **PD140V** and **PD140VR** (model equipped for no-contact induction battery charger). Both are available with a 9V dry battery or rechargeable Ni/MH batteries.

TECHNICAL FEATURES

PD140VR: 9V NiMH with BC140F inductive charger PREE-POSITION SWITCH WITH SELECTION DF TWO DIFFERENT ALARM MODES Simultaneous optical and acoustic alarm. Built-in buzzer (75 dBA at a distance of 90 cm) Optical alarm and handle vibration Optical alarm and handle vibration SENSITIVITY ADJUSTMENT BY MEANS OF A THREE-POSITION EXTERNAL SELECTOR With alkaline batteries: 150 hours max with NiMH batteries: 40 hours max NDICATOR LAMPS FOR Power on (green light) Alarm (red light) Low battery charge (blinking yellow light) OPERATING TEMPERATURE -15°C to 65°C (relative humidity: 0 to 95%) Manufactured in grey, shock-resistant Polycarbonate and ABS blend 340 x 80 x 55 mm VEIGHT (WITH BATTERY) 0.400 kg Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable		
HREE-POSITION SWITCH WITH SELECTION OF TWO DIFFERENT ALARM MODES Simultaneous optical and acoustic alarm. Built-in buzzer (75 dBA at a distance of 90 cm) Optical alarm and handle vibration Optical alarm and handle vibration SENSITIVITY ADJUSTMENT BY MEANS OF A THREE-POSITION EXTERNAL SELECTOR with alkaline batteries: 150 hours max BATTERY LIFE IN CONTINUOUS OPERATION with alkaline batteries: 40 hours max NDICATOR LAMPS FOR Power on (green light) Alarm (red light) Low battery charge (blinking yellow light) OPERATING TEMPERATURE -15°C to 65°C (relative humidity: 0 to 95%) Manufactured in grey, shock-resistant Polycarbonate and ABS blend 340 x 80 x 55 mm VEIGHT (WITH BATTERY) 0.400 kg Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable	POWER SUPPLY	or 9V NiMH with contact charger
HREE-POSITION SWITCH WITH SELECTION OF TWO DIFFERENT ALARM MODES Built-in buzzer (75 dBA at a distance of 90 cm) Optical alarm and handle vibration SENSITIVITY ADJUSTMENT BY MEANS OF A THREE-POSITION EXTERNAL SELECTOR with alkaline batteries: 150 hours max with NiMH batteries: 40 hours max BATTERY LIFE IN CONTINUOUS OPERATION Mith alkaline batteries: 40 hours max NDICATOR LAMPS FOR Power on (green light) Low battery charge (blinking yellow light) OPERATING TEMPERATURE -15°C to 65°C (relative humidity: 0 to 95%) Manufactured in grey, shock-resistant Polycarbonate and ABS blend 340 x 80 x 55 mm VEIGHT (WITH BATTERY) 0.400 kg Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable		PD140VR: 9V NiMH with BC140F inductive charger
Optical alarm and handle vibration SENSITIVITY ADJUSTMENT BY MEANS OF A THREE-POSITION EXTERNAL SELECTOR With alkaline batteries: 150 hours max With alkaline batteries: 40 hours max With NIMH batteries: 40 hours max NDICATOR LAMPS FOR Power on (green light) Alarm (red light) Low battery charge (blinking yellow light) OPERATING TEMPERATURE -15°C to 65°C (relative humidity: 0 to 95%) Manufactured in grey, shock-resistant Polycarbonate and ABS blend DIMENSIONS 340 x 80 x 55 mm VEIGHT (WITH BATTERY) 0.400 kg Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable	THREE-POSITION SWITCH WITH SELECTION OF TWO DIFFERENT ALARM MODES	
BATTERY LIFE IN CONTINUOUS OPERATION with alkaline batteries: 150 hours max with NiMH batteries: 40 hours max with NiMH batteries: 40 hours max Power on (green light) Alarm (red light) Low battery charge (blinking yellow light) OPERATING TEMPERATURE -15°C to 65°C (relative humidity: 0 to 95%) Manufactured in grey, shock-resistant Polycarbonate and ABS blend DIMENSIONS YEIGHT (WITH BATTERY) Outor on grey to the international standards currently applicable for electrical safety, E.M.C. and to the applicable		Optical alarm and handle vibration
BATTERY LIFE IN CONTINUOUS OPERATION with NiMH batteries: 40 hours max with NiMH batteries: 40 hours max Power on (green light) NDICATOR LAMPS FOR Alarm (red light) DPERATING TEMPERATURE -15°C to 65°C (relative humidity: 0 to 95%) Aanufactured in grey, shock-resistant Polycarbonate and ABS blend DIMENSIONS 340 x 80 x 55 mm VEIGHT (WITH BATTERY) 0.400 kg Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable	SENSITIVITY ADJUSTMENT BY MEANS OF A THREE-POSITION EXTERNAL SELECTOR	
with NiMH batteries: 40 hours max Power on (green light) Alarm (red light) Low battery charge (blinking yellow light) operating temperature -15°C to 65°C (relative humidity: 0 to 95%) Manufactured in grey, shock-resistant Polycarbonate and ABS blend DIMENSIONS 340 x 80 x 55 mm VEIGHT (WITH BATTERY) 0.400 kg Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable	BATTERY LIFE IN CONTINUOUS OPERATION	with alkaline batteries: 150 hours max
NDICATOR LAMPS FOR Alarm (red light) Low battery charge (blinking yellow light) DPERATING TEMPERATURE -15°C to 65°C (relative humidity: 0 to 95%) Manufactured in grey, shock-resistant Polycarbonate and ABS blend DIMENSIONS 340 x 80 x 55 mm VEIGHT (WITH BATTERY) 0.400 kg Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable		with NiMH batteries: 40 hours max
Low battery charge (blinking yellow light) DPERATING TEMPERATURE -15°C to 65°C (relative humidity: 0 to 95%) Manufactured in grey, shock-resistant Polycarbonate and ABS blend DIMENSIONS 340 x 80 x 55 mm VEIGHT (WITH BATTERY) 0.400 kg Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable	INDICATOR LAMPS FOR	Power on (green light)
OPERATING TEMPERATURE -15°C to 65°C (relative humidity: 0 to 95%) Manufactured in grey, shock-resistant Polycarbonate and ABS blend DIMENSIONS 340 x 80 x 55 mm VEIGHT (WITH BATTERY) 0.400 kg Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable		Alarm (red light)
Anufactured in grey, shock-resistant Polycarbonate and ABS blend DIMENSIONS 340 x 80 x 55 mm VEIGHT (WITH BATTERY) 0.400 kg Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable		Low battery charge (blinking yellow light)
DIMENSIONS 340 x 80 x 55 mm VEIGHT (WITH BATTERY) 0.400 kg Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable	OPERATING TEMPERATURE	-15°C to 65°C (relative humidity: 0 to 95%)
VEIGHT (WITH BATTERY) 0.400 kg Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable	Manufactured in grey, shock-resistant Polycarbonate and ABS blend	
Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable	DIMENSIONS	340 x 80 x 55 mm
	WEIGHT (WITH BATTERY)	0.400 kg
	Conforms to the international standards currently ap CE regulations	oplicable for electrical safety, E.M.C. and to the applicable

BC140F FAST INDUCTIVE BATTERY CHARGER

The BC140F unit provides recharging, without electrical contact, of the NiMH batteries in the PD140VR Metal Detectors. The BC140F battery charger is designed to be able to be connected in cascade with other similar devices.

TECHNICAL FEATURES

POWER SUPPLY: 90-265Vrms, 50/60 Hz, 4 W

- **RECHARGING TIME:** 4 hours or less (complete cycle)
- **ON/OFF** switch with indicator lamp

Connection in cascade with other similar devices (up to 20 units)

DIMENSIONS: 82 x 155 x 97 (h) mm

WEIGHT: 0.500 kg

LENGTH OF MAINS CABLE: 1.80 m

Length of cable for connecting units in cascade: 0.17 m

Manufactured in grey, shock-resistant ABS

Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable CE regulations

V140 CARRYING CASE

The V140 carrying-case, in shock-resistant material, is designed to contain the following items: a PD140 Hand Held Metal Detector, a test piece, a BC140F fast battery-charger, a power supply cable and the instructions for use.

TECHNICAL FEATURES

DIMENSIONS: 445 x 300 x 180 mm WEIGHT: 2.300 kg including PD140 and battery

charger

Shock-resistant ABS construction and the special storage compartments make the V140 carrying-case the ideal, safest and most compact means of transporting the PD140

Conforms to the international standards currently applicable for electrical safety, E.M.C. and to the applicable CE regulations



OPERATOR CONTROLS

 ALARM Red Light: Alarm Signalling
 LOW BATTERY Yellow light: Low Battery Signalling (blinking)
 POWER Green light: "Power on" and "Ready" status Signalling. When charging on the BC140F, indicates the status of the charge
 SENSITIVITY ADJUSTMENT
 POWER/MODE Switch
 Left position: visual and audible alarm signalling
 Right position: visual and vibration

alarm signalling
6 ALARM BUZZER



1000211K 100K2V3



Zona Industriale 54/G, 52041 Viciomaggio - Arezzo (ITALY) Tel.: +39 0575 4181 Fax: +39 0575 418298 E-mail: infosecurity@ceia-spa.com

www.ceia.net